

## 1. Product Description

**StenSilan® WO** is a single-component, silane-based, water and oil repellent impregnation agent. **StenSilan® WO** bonds chemically to mineral surfaces like natural stone, concrete, plaster and makes these surfaces hydrophobic (water-repellent) and oleophobic (oil repellent). Surfaces treated with **StenSilan® WO** do not get wet or soiled by water, oil and many similar liquids.

It is a low viscosity transparent liquid; it has strong surface-covering and material-penetration properties. It does not form a separate layer on concrete; instead, it imparts hydrophobic and oleophobic properties to the concrete. Consequently, hydrophobic and oleophobic properties remain until the upper layers of the concrete are completely worn away, and there is no danger of the coating peeling, separating, becoming brittle or slippery over time, as encountered in impregnation-type materials.

## 2. Uses

**StenSilan® WO** prevents gas-permeable, breathable mineral surfaces such as concrete, plaster, aerated concrete, natural stone, and ceramic from absorbing water and oil. By bonding chemically with these materials and diffusing into the surface, it makes them hydrophobic and oleophobic, including on hairline crack surfaces, and keeps liquids from entering the structure. Liquids left on the surface can be easily cleaned by wiping and leave no stain.

Since **StenSilan® WO** does not clog capillary channels, it does not impede the structure's ability to breathe or transmit gases. It considerably prolongs the coating life by preventing capillary cracks from widening and damaging the surface when the water that has penetrated into them freezes. Since the thermal conductivity of materials increases when they absorb water, it contributes indirectly to thermal insulation by keeping the surface dry.

The natural appearance of the surfaces does not change when **StenSilan® WO** is applied; it does not form a hydrophobic coating that may separate from the surface. Because of these properties, **StenSilan® WO** is used to protect all kinds of concrete and various mineral surfaces that are open to atmospheric conditions and to the wetting action of rainwater or water from other sources. It is ideal for protection of floors at workshops, repair shops and factories where contaminants that can stain or degrade concrete are present.

**StenSilan® WO** maintains its hydrophobic and oleophobic properties for 5-10 years depending on the penetration depth and surface abrasion. At the end of these periods, **StenSilan® WO** application must be repeated.

## Solvent-Borne Silane Water-Repellent Impregnation

### Highlights

- Single-component, silane-based
- Low viscosity transparent fluid
- Allows the surface to breathe and preserves its natural appearance
- Strong surface-covering and material-penetration properties
- Impregnates the surface; makes it water- and oil-repellent in depth without forming a film
- Liquids on the surface can be easily cleaned by wiping and leave no stain
- Resistant to UV radiation and increases the durability of the coated surface
- Prevents salt efflorescence on absorptive surfaces during drying
- Improves the paintability of the treated surface
- Can be applied by spraying or manually with a brush and roller



## 3. Application

### 3.1. Application

The surface must be cleaned, dust and loose material removed, and cracks repaired before application. Contaminants such as fuel, oil and chemicals must be removed. It is advised to perform a small test application before full application and record the consumption.

To test, 24 hours after application, drip contaminants such as water, coffee and olive oil onto the surface, leave them for 2 hours, then wipe clean. When applied in the correct amount on compatible substrates, no mark will remain on the surface. Unlike other water-repellents, this product does not have a beading effect, so it is important not to judge effectiveness by whether contaminating liquids bead on the surface.

Application can be carried out on moist or dry surfaces. However, it is required to protect the material from water contact and rain until the applied material dries. **StenSilan® WO** is applied by spraying or by brush and roller.

It is sufficient if the surface is wetted with **StenSilan® WO** during the application. The consumption is 4 to 20 m<sup>2</sup>/l depending on the surface properties and desired protection level. Excessive application of **StenSilan® WO** may result in a wet look.

On highly absorbent substrates a second application might be necessary. In this case, the second coat must be applied wet-on-wet, while the first is still wet. The depth of the water-repellent layer can be increased by using more material, but it must be borne in mind that this may affect the appearance of the surface.

Products in opened packages must be used as soon as possible. If the whole package will not be used, a sufficient amount must be transferred to another container and the package must be reclosed tightly. Tools used must be cleaned at the end of the job.

Since the material may adhere to all materials including glass, it must not get onto unintended surfaces. In indoor applications, application must be carried out after the furnishings and plants are covered. Turbid or partially cured material must not be used.

### 3.2. Cleaning

Equipment used can be cleaned at the end of the job with **StenSolver CL**.

## 4. Safety

Applicators and supervisors must read the Safety Data Sheet (SDS) carefully and follow the instructions provided. Emptied packages must be disposed of in compliance with relevant regulations and laws. The application must be carried out by skilled workers under the supervision of experts and the applicators must use all personal protective equipment required for the worksite and the task such as goggles, mask and gloves.

## 5. Storage

Packages must not be exposed to direct sunlight. It must be stored away from open flames and ignition sources. Storage temperature must be between 5 and 30 °C. Under these conditions, the material will retain its properties in unopened containers for 6 months from the production date. The material is flammable. After prolonged storage, the product must be stirred thoroughly before use.



## 6. Disclaimer

This document is provided for general information and is based on **Stenkim**<sup>®</sup>'s laboratory data and field experience at the time of publication. **Stenkim**<sup>®</sup> reserves the right to revise this information without prior notice.

**Stenkim**<sup>®</sup> warrants that its products conform to the stated specifications on delivery. The buyer is responsible for determining the product's suitability for the intended purpose and for all conditions of transport, storage, application, and use. **Stenkim**<sup>®</sup> accepts no liability for results obtained under conditions outside its control. **Stenkim**<sup>®</sup>'s liability under this warranty is limited to replacement of non-conforming product and excludes any consequential or indirect damages.

## 7. Technical Data

| Property      | Method        | Result                        |
|---------------|---------------|-------------------------------|
| Consumption   |               | 0.05-0.25 l/m <sup>2</sup>    |
| Density       | EN ISO 2811-2 | 0.82 ± 0.05 g/cm <sup>3</sup> |
| Concentration |               | min. 50%                      |
| Shelf Life    |               | 6 months                      |
| Packaging     |               | 10 liter packages             |

**Stenkim**<sup>®</sup> reserves the right to make changes to the values in this table at any time.

