

1. Product Description

StenSolver CL is the general-purpose cleaner in the StenSolver product family. **StenSolver CL** contains xylene. It has high solvency, evaporates quickly, and is not miscible with water. **StenSolver CL** is designed for cleaning tools and surfaces contaminated with all polymeric materials manufactured by **Stenkim®**.

General-Purpose Solvent and Cleaning Agent

2. Uses

StenSolver CL is used for cleaning tools and surfaces contaminated with all polymeric materials manufactured by **Stenkim®**. It is used to clean equipment contaminated with these materials before the material hardens. Hardened material residues can be softened by soaking in a suitable solvent, making them easier to remove.

StenSolver CL can also be used for pre-cleaning the application area. It is used to remove contaminants such as asphalt, bitumen, and oil from the surfaces to be cleaned. Using **StenSolver CL** to clean material residue from joint edges or the surface is not recommended. During cleaning, it leaves a thin film that stains the surface. In such cases, the material must be left to dry without wiping, and after drying it must be removed mechanically. Where edge cleanliness is important, it is recommended to mask the joint edges with tape before applying joint sealant.

3. Warnings

- **StenSolver** products are for professional use.
- As it is flammable, smoking must be avoided during use and it must be kept away from open flames and sources of sparks.

In enclosed areas, adequate ventilation must be provided and prolonged inhalation of vapors must be avoided.

- It must be ensured that users use protective equipment such as masks, goggles, and gloves and take the necessary safety precautions.
- In case of contact with eyes, rinse with plenty of water and consult a doctor for medical treatment.
- People prone to allergic reactions must not use this product.
- It must be taken into account that, as it is a strong solvent, it may affect some organic materials.
- Opened containers must be closed after work is completed, and empty containers must be disposed of in accordance with regulations.

4. Safety

Applicators and supervisors must read the Safety Data Sheet (SDS) carefully and follow the instructions provided. Emptied packages must be disposed of in compliance with relevant regulations and laws. The application must be carried out by skilled workers under the supervision of experts and the applicators must use all personal protective equipment required for the worksite and the task such as goggles, mask and gloves.

5. Storage

Packages must not be exposed to direct sunlight. It must be stored away from open flames and ignition sources. Storage temperature must be between 5 and 30 °C. Under these conditions, the material will retain its properties in unopened packages until the expiration date.



6. Disclaimer

This document is provided for general information and is based on **Stenkim®**'s laboratory data and field experience at the time of publication. **Stenkim®** reserves the right to revise this information without prior notice.

Stenkim® warrants that its products conform to the stated specifications on delivery. The buyer is responsible for determining the product's suitability for the intended purpose and for all conditions of transport, storage, application, and use. **Stenkim®** accepts no liability for results obtained under conditions outside its control. **Stenkim®**'s liability under this warranty is limited to replacement of non-conforming product and excludes any consequential or indirect damages.

