

1. Product Description

StenSolver EP is the member of the StenSolver product family designed as a solvent and thinner for solvent-based epoxy products. **StenSolver EP** is a mixture of xylene, methyl ethyl ketone (MEK) and isopropyl alcohol (IPA). It has high solvency, evaporates quickly, and is not miscible with water. **StenSolver EP** is designed for cleaning and thinning solvent-based epoxy materials manufactured by **Stenkim®**.

**Solvent and Thinner for
Solvent-Based Epoxy
Products**

2. Uses

StenSolver EP is used for cleaning and thinning solvent-based epoxy products manufactured by **Stenkim®**. It is used to clean equipment contaminated with these materials before the material hardens. Hardened material residues can be softened by soaking in a suitable solvent, making them easier to remove. In two-component epoxy formulations, **StenSolver EP** is added to Component A before components A and B are combined.

3. Warnings

- **StenSolver** products are for professional use.
- As it is flammable, smoking must be avoided during use and it must be kept away from open flames and sources of sparks.

In enclosed areas, adequate ventilation must be provided and prolonged inhalation of vapors must be avoided.

- It must be ensured that users use protective equipment such as masks, goggles, and gloves and take the necessary safety precautions.
- In case of contact with eyes, rinse with plenty of water and consult a doctor for medical treatment.
- People prone to allergic reactions must not use this product.
- It must be taken into account that, as it is a strong solvent, it may affect some organic materials.
- Opened containers must be closed after work is completed, and empty containers must be disposed of in accordance with regulations.

4. Safety

Applicators and supervisors must read the Safety Data Sheet (SDS) carefully and follow the instructions provided. Emptied packages must be disposed of in compliance with relevant regulations and laws. The application must be carried out by skilled workers under the supervision of experts and the applicators must use all personal protective equipment required for the worksite and the task such as goggles, mask and gloves.

5. Storage

Packages must not be exposed to direct sunlight. It must be stored away from open flames and ignition sources. Storage temperature must be between 5 and 30 °C. Under these conditions, the material will retain its properties in unopened packages until the expiration date. The material is flammable.

6. Disclaimer

This document is provided for general information and is based on **Stenkim®**'s laboratory data and field experience at the time of publication. **Stenkim®** reserves the right to revise this information without prior notice.



Stenkim® warrants that its products conform to the stated specifications on delivery. The buyer is responsible for determining the product's suitability for the intended purpose and for all conditions of transport, storage, application, and use. **Stenkim®** accepts no liability for results obtained under conditions outside its control. **Stenkim®**'s liability under this warranty is limited to replacement of non-conforming product and excludes any consequential or indirect damages.

