

1. Product Description

Stenkim® CT 2 is a dark-colored, fluid raw material based on processed coal tar. It provides high resistance to water, chemicals and penetration. This product is not offered for sale in EU and EFTA countries.

2. Uses

Stenkim® CT 2 is used as a raw material in the production of coal-tar epoxy coatings and certain marine paints. It imparts high water and chemical resistance to formulations.

3. Safety

Applicators and supervisors must read the Safety Data Sheet (SDS) carefully and follow the instructions provided. Emptied packages must be disposed of in compliance with relevant regulations and laws.

4. Storage

Storage temperature must be between 5 and 30 °C. Packages must not be exposed to direct sunlight and must be stored away from heat and sources of flame.

5. Disclaimer

This document is provided for general information and is based on **Stenkim®**'s laboratory data and field experience at the time of publication. **Stenkim®** reserves the right to revise this information without prior notice.

Stenkim® warrants that its products conform to the stated specifications on delivery. The buyer is responsible for determining the product's suitability for the intended purpose and for all conditions of transport, storage, application, and use. **Stenkim®** accepts no liability for results obtained under conditions outside its control. **Stenkim®**'s liability under this warranty is limited to replacement of non-conforming product and excludes any consequential or indirect damages.

6. Technical Data

Property	Method	Result
Appearance - Color		Dark-colored liquid
Water Content	ASTM D86 / ASTM D95	Contains No Water
Density	EN ISO 2811-2	1.1 ± 0.1 g/cm ³
CS ₂ -Insoluble Matter	ASTM D4	27%
Fineness of Grind (Grindometer)	TS 2620 EN ISO 1524	30-40 µm
Volatile Content	ASTM D1075	19% ± 1%

Stenkim® reserves the right to make changes to the values in this table at any time.

Processed Coal Tar (Raw Material)

Highlights

- Processed, high-purity coal tar
- Provides high water and chemical resistance
- Low volatile content

